

# USB 3.0/2.0/1.1 Single LC Fiber Extender : 1 port USB-B to 4 port USB-A





#### TX USB 3.0 Type-B receptacle

OV14UBA-1FO-321

#### **Features**

- > Host and Device units are Compatible with USB3.0/ USB2.0/1.1.
- > Distance up to 300m for USB3.0 storage devices, 100m for USB3.0 cameras.
- > Pure hardware design, no driver needed, support plug and play.
- > Support USB 3.0 super speed up to 5Gbps.
- Support Kinect devices.
- > Device unit Integrated 4 port USB3.0 /2.0/1.1 hub, the max. output current of each port is 1A.
- Compliant with Windows 8, Windows 8.1, Windows 10, full version of the Linux or Unix operation systems.

#### **Specification**

Data Rate	USB 3.0: 5Gbps
	USB 2.0: 48Mbps
	USB 1.1: 12Mbps
Case	Metal
Color	Black
Distance	Data signal: 300 Meter(984ft)
	Video signal: 100 Meter(328ft)
USB Compatible	3.0/2.0/1.1
Voltage	12V DC
Dimension(LxWxH)	TX: 110x75x26mm
	RX: 135x85x26mm
	Package: 220x160x120mm
Weight	TX: 346g RX: 435g
	Package:1.26kg
Environment	Operating Temperature : -10°C~60°C
	Storage Temperature : -45°C~+85°C

### Optical

- Optical Fiber: Single-mode fiber or OM3 Multimode fiber
- Distance:

Data signal: 300M(984ft)

Video signal: 100M(328ft)

## **Application**



## www.optav-tech.com

5th floor, High-tech industrial park, NO.1 Dezheng Road, Shilong Community, Bao'an District, Shenzhen, China +86.137.2421.5827 freya@optav-tech.com