

## USB 3.2/2.0/1.1 Single LC Fiber Extender: 1 port USB-A to 4 port USB-A



### TX USB 3.0 Type-A receptacle

OV14UAA-1FO-321

### Features

- Host and Device units are Compatible with USB3.2 GEN 1/ USB2.0/1.1.
- Max extension distance 100m for graphic and 300m for data.
- Pure hardware design, no driver needed, support plug and play.
- Data rate up to 5Gbps.
- Device unit Integrated 4 port USB3.2 Gen 1 /2.0/1.1 hub.
- Compliant with Windows 8, Windows 8.1, Windows 10, full version of the Linux or Unix operation systems.
- Small size and easy installation.

### Specification

	TX	RX
USB Interface	USB Type-A Male x 1	USB Type-A Female x 4
Enclosure Material	Zinc Alloy	Metal
Voltage	No power supply required	DC 12V
Distance	Data signal: 300 Meter(984ft) Video signal: 100 Meter(328ft)	
USB Compatible	3.2 GEN 1/2.0/1.1	
Dimension(LxWxH)	TX: 62x20x10.5mm	RX: 135x75x26mm
	Package: 220x160x120mm	
Weight	TX: 346g	RX: 345g
	Package: 1.26kg	
Environment	Operating Temperature : -10°C~60°C Storage Temperature : -45°C~+85°C	

### Optical

- Optical Fiber: Single-mode fiber or OM3 Multi-mode fiber
- Distance:  
Data signal: 300M(984ft)  
Video signal: 100M(328ft)

### Application

