

DP 1.4 Full 8K Single Optical Fiber Extender (LC Single-mode) with HDMI out



Specification

	Transmitter	Receiver
DP compliance	DP1.4/DP1.2	
Video Bandwidth	32.4Gbps	
Distance	Single-mode fiber: 1000M	
Supporting Resolution	8K@30HZ 4K@120HZ	
Connector/Fiber	DP(female)/ HDMI(female)/LC	
CWDM filter	Integrated 1270nm/1290nm/1310nm /1330nm/1490nm/1550nm filter	
Power Supply	12V/2A	
Power Consumption	3W	3W
Color	Black	Black
Dimension(LxWxH)	Model: 160x85x26 (mm)	Model: 160x85x26 (mm)
	Package: (mm)	
Weight	Model:500 g	Model: 500g
	Package: 1500 g	
Environment	Operating Temperature Range: -10°C~60°C Storage Temperature Range: -40°C~85°C	
Relative Humidity	5-95% RH (no condensation)	

OV12DP-1FO-014

Features

- > CWDM Single Fiber Technology.
- 1270/1290/1310/1330/1490/1550nm DFB lasers inside.
- > Compliant with DP1.2 and DP1.4.
- > AUX signal Transparent pass-through.
- > Extension distance up to 1000 meters.
- Transmit signal over one Single-mode LC
 Fiber.
- Uncompressed video up to 32.4Gb/s data rate.
- > Maximum resolution up to8k@30Hz.
- > Bi-directional RS-232 and IR extension.
- > Zero frame delay.
- > HDR and Dolby Vision support.
- Support DP and HDMI output simultaneously.

Optical

- Optical source: CWDM DFB laser
- > Fiber: 1 core LC, Single mode
- Distance: 1000M

Package

- ≻ TX x 1
- ≻ RX x 1
- > 12V/2A power adapter x 2
- > IR receiver cable x 1
- IR emitter cable x 1
- Phoenix terminal(male) x 2

www.optav-tech.com

5th floor, High-tech industrial park, NO.1 Dezheng Road, Shilong Community, Bao'an District, Shenzhen, China +86.137.2421.5827 freva@optav-tech.com